


Identity: As used on Label and List

LF PRIMER, POLY-BOND


U.S. Department of Labor
 Occupational Safety & Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

NFPA ratings (scale 0 - 4)



Health = 1
 Fire = 0
 Reactivity = 0

HMIS-ratings (scale 0 - 4)



Health = 1
 Fire = 0
 Reactivity = 0

Section 1 – Company Identification

| | | |
|---|---|--|
| Manufacturer's Name CMP Specialty Products, Inc | Emergency Phone Number 215.672.6364 | Address (Number, Street, City, and Zip) PO Box 3164 Maple Glen, PA 19002 |
| Information Phone Number 215.672.6364 | FAX Number: 215.672.6384 | Preparation Date January 1, 2007 |

Section II – Hazardous Ingredients / Identity Information

| CAS Number | WT % | Material | OSHA PEL | ACGIH TLV |
|------------|---------|-------------------------|----------------------|----------------------|
| 24937-78-8 | 40-60 % | Styrene Acrylic Polymer | 10 mg/m ³ | 10 mg/m ³ |
| 7732-18-5 | 40-60 % | Water | - | - |

Section III - Physical/Chemical Characteristics

| | | |
|------------------------------------|--|---|
| Boiling Point 212°F | Specific Gravity (H2O = 1) 1.1 | Vapor Pressure (mm Hg.) 17 @ 20°F |
| pH (wet state) 5.5 – 8.5 | Vapor Density (AIR = 1) .7 | Solubility in Water 100% |
| Melting point 32°F | Evaporation Rate <1 | Appearance and Odor White Liquid |

Section IV - Fire and Explosion Hazard Data

| | | |
|---|---|---|
| Flash Point Non-Flammable | Flammable Limits Non-Flammable | LEL/UEL N/A |
| Extinguishing Media Will Not Burn | Special Fire Fighting Procedures None | Unusual Fire & Explosion Hazards None |

Section V - Reactivity Data

| | | |
|--|--|---|
| Stability Stable | Conditions to Avoid Protect from freezing or boiling | Incompatibility (Materials to Avoid) Reactive metals (sodium, calcium, zinc.....) |
| Hazardous Decomposition Will not occur | Hazardous Polymerization Will not occur | Conditions to Avoid N/A |

Section VI - Health Hazard Data**Health Hazards****ACUTE:**

EYES: Contact with eyes will cause irritation and possible corrosion damage and burning. Particulates can also cause mechanical irritation.

SKIN: When mixed with water, direct contact with skin can cause irritation. If irritation occurs, rinse with water until free of material, then wash skin thoroughly with soap and water.

INHALATION: Remove to fresh air until irritation subsides, if continues consult physician.

INGESTIONS: See medical attention immediately.

CHRONIC:

EYES: None known

SKIN: None known

INHALATION: None known

PRIMARY ROUTES OF ENTRY: Inhalation, eyes and/or skin contact, ingestion.

Section VII - Precautions for Safe Handling and Use**Steps to Be Taken in Case Material is Released or Spilled**

Spilled material can produce slippery conditions, be cautious to avoid falling. Wear appropriate protective equipment. Dike material with soil or other appropriate material to prevent spreading. A film will form on drying, Shovel material from spilling into a waste container for disposal.

Waste Disposal Method

Dispose of in accordance with all applicable local, State/Provincial and Federal regulations.

Precautions to Be Taken in Handling and Storing

Store in a cool, dry area. Take precautions to avoid bag breakage, subsequent spillage of material and dust creation.

Section VIII - Control Measures**Respiratory Protection**

Wear proper respiratory protection during mixing and during sanding if needed. Provide general ventilation and local exhaust ventilation to meet TLV requirements of individual ingredients and to control dusting conditions. Wear a NIOSH/MSHA approved respirator in poorly ventilated dusty areas and/or if TLV is exceeded.

Ventilation

Ventilate to keep exposures below TLV. General ventilation is expected to be satisfactory in most cases. Use local exhaust ventilation if necessary to control dust.

Protective Clothing or Equipment

Gloves or protective clothing are usually not necessary but may be desirable in work situations. Wear gloves and protective clothing to prevent repeated skin contact. Wear eye protection (safety glasses or goggles) to avoid corrosion and irritation of the eye. Work/Hygienic Practices When finished, shower with soap and water to remove dust. Dusty clothing should be laundered before reuse.